RELIABLE CONTAINERS

Harlequin[®] torageTanks

Harlequin 1000ITT **Bunded Fuel Tank**

Tank Dimensions:

Length: 2150mm Width: 690mm

Overall Height: 1420mm Brimful Capacity: 1055L Nominal Capacity: 1003L

Net Weight: 132kg



Harlequin ITT bunded top offtake oil tanks come equipped with a range of standard fittings, including an Atkinson Tanktop and ultrasonic contents gauge – the safest and most complete solution for a fully compliant installation.

Standard Features:

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Atkinson Tanktop top offtake fitting (c/w integral anti-siphon valve, non-return valve, 50Mic filter & priming button)
- 16" lockable access lid
- 2" BSP(M) fill point
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- Inner tank vent
- Moulded-in handles for ease of lifting

Issued By:

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL139d Issue Date: February 2020 Issue: 01 Revision 05

Auth: JC