# Harlequin<sup>®</sup> torageTanks

## Harlequin 1225ITT **Bunded Fuel Tank**

### RELIABLE CONTAINERS

#### **Tank Dimensions:**

Length: 2110mm Width: 840mm

Overall Height: 1525mm Brimful Capacity: 1248L Nominal Capacity: 1186L

Net Weight: 150kg



Harlequin ITT bunded top offtake oil tanks come equipped with a range of standard fittings, including an Atkinson Tanktop and ultrasonic contents gauge – the safest and most complete solution for a fully compliant installation.

#### **Standard Features:**

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Atkinson Tanktop top offtake fitting (c/w integral anti-siphon valve, non-return valve, 50Mic filter & priming button)
- 16" lockable access lid
- 2" BSP(M) fill point
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- LRC overfill prevention probe
- Inner tank vent
- Moulded-in handles for ease of lifting

#### **Issued By:**

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL226c Issue Date: June 2018 Issue: 01 Revision 00

Auth: JC