# **Harlequin**<sup>®</sup> torageTanks

#### RELIABLE CONTAINERS

### **Tank Dimensions:**

Length: 2940mm Width: 2305mm

Overall Height: 2820mm Brimful Capacity: 8,088L Nominal Capacity: 7,683L

Net Weight: 505kg

## Harlequin 7500ITE **Bunded Fuel Tank**



Harlequin ITE bunded oil tanks come equipped with a range of standard fittings, including an ultrasonic contents gauge and bottom outlet fitting kit – the complete solution for a fully compliant installation.

### **Standard Features:**

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- Lockable equipment cabinet
- 2" BSP(M) offset fill point c/w non-return valve & lever ball valve
- Mechanical overfill prevention valve
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- Bottom outlet fitting kit (reducer, isolation valve, filter, 10mm oil line fitting)
- LRC overfill prevention probe
- **Bund monitor**
- Moulded-in lifting eyes for ease of handling

### **Issued By:**

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL227b Issue Date: September 2019 Issue: 01 Revision 01

Auth: JC